



## TEL-7001

### Telaire 7001 CO2 Sensor

The Telaire 7001 handheld carbon dioxide sensor features patented absorption infrared technology. Each sensor measures CO<sub>2</sub> and temperature and can calculate and display real-time ventilation rates. When combined with the HOBO MX1104, MX1105, or UX120-006M, it can record CO<sub>2</sub>. When connected to analog inputs on a HOBO H22, RX3000, or U30 series logger, it can record temperature and CO<sub>2</sub>. The Telaire comes with a power adapter, but also operates up to 70 hours on 4 AA batteries (not included).



#### Key Advantages:

- Record 0 to 2500 ppm when using the CABLE-CO2 and a HOBO U12, UX120-006M, MX1100, or ZW series logger
- Record 0 to 4000 ppm when using the CABLE-2070 and a HOBO RX3000, H22, or U30 data logger
- AC power adapter included

## HOBO TEL-7001 Sensor Specifications

### Measurement Range

**When using the CABLE-CO2 and a U12 or ZW:** 0 to 2500 ppm

**When using the CABLE-2070 and a H22 or U30:** 0 to 4000 ppm

**Telaire 7001 operating range:** 32°F to 122°F (0°C to 50°C), 0 to 95% RH, non-condensing

**Display resolution:** ±1 ppm

**Accuracy:** ±50 ppm or 5% of reading, whichever is greater

**Repeatability:** ±20 ppm

**Temperature dependence:** ±0.1% of reading per °C or ±2 ppm per °C, whichever is greater, referenced at 25°C.

**Pressure dependence:** 0.13% of reading per mmHg (corrected via user input for elevation)

**Response time:** <60 seconds for 90% of step change

**Warm-up time:** <60 seconds at 72°F (22°C)

**Calibration interval:** 12 months Full factory calibration available by contacting GE Measurement & Control Solutions.

**Battery type:** Four AA batteries (not included)

**Battery operation:** 80 hours (alkaline)

### External power supply specifications

#### AC/DC adapter (included)

**Output:** 6 VDC, 500mA output.

**Power connector:** Round barrel with 2.5mm ID , 5.5mm OD, 12mm long, center positive (+6 VDC), outer shell ground.

## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

▶ Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-800-564-4377

▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

▶ Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532