


Silhouette-Based Segmentation of 3D Objects for Industrial Use Cases

Felix Stieglbauer

22.09.2022



Guided Research

Advisors: Linda Rudolph, Daniel Dyrda


Supervisor: Prof. Gudrun Klinker, Ph.D.

Motivation



Source: 1)

Motivation



Source: 1)

Motivation

Remote maintenance

and

AR-based navigation

Motivation

Problem: Scene changes frequently

→ Complete scans pointless / not feasible

Motivation

Problem: Scene changes frequently

→ Complete scans pointless / not feasible

Solution: Scan iteratively!

Motivation




Source: 2)

Motivation

New problem:

The scanner needs to know what to scan



Source: 2)


Motivation

New problem:


The scanner needs to know what to scan

We will
solve this!



Related work



Scope, source: 3)



Worm Selector, source: 4)



Go'then'tag, source: 5)

Requirements

- Visual guidance
- Speed
- Spatial limitation
- Complex three-dimensional setups
- Pen-based input

Requirements



Source: 6)

Requirements

- Visual guidance
- Speed
- Spatial limitation
- Complex three-dimensional setups
- Pen-based input

Requirements




Source: 2)

Requirements

- Visual guidance
- Speed
- Spatial limitation
- Complex three-dimensional setups
- Pen-based input

Requirements



Source: 7)

Requirements




Source: 7)

Requirements


- Visual guidance
- Speed
- Spatial limitation
- Complex three-dimensional setups
- Pen-based input

Approach





Source: 2)

Approach



Approach




Approach

Let's see it in action!

Evaluation

- Visual guidance ✓
- Speed ✓
- Spatial limitation ✓
- Complex three-dimensional setups ✓
- Pen-based input ✓


Evaluation – visual guidance



Evaluation

- Visual guidance ✓
- Speed ✓
- Spatial limitation ✓
- Complex three-dimensional setups ✓
- Pen-based input ✓


Outlook – compensating faulty measurements




Outlook – compensating faulty measurements



Outlook – compensating faulty measurements



Outlook – enhancing performance





Thank you very much!

List of References

- 1) <https://matrixti.com/matrix-on-manufacturing/3d-laser-scanning-industrial-plant-design/>
- 2) L. Rudolph and G. Klinker. As-built Industrial Scene Reconstruction based on Photogrammetry and Prior-Knowledge for Extended Reality Scenarios. In *2021 IEEE International Symposium on Mixed and Augmented Reality Adjunct (ISMAR-Adjunct)*, pp. 480-482. IEEE, 2021.
- 3) J. Cashion and J. J. LaViola. Dynamic adaptation of 3d selection techniques for suitability across diverse scenarios. In *2014 IEEE Symposium on 3D User Interfaces (3DUI)*, pp. 165–166. IEEE, 2014.
- 4) E. Dubois and A. Hamelin. Worm selector: volume selection in a 3d point cloud through adaptive modelling. *The International Journal of Virtual Reality*, 17(1):1–20, 2017.
- 5) M. Veit and A. Capobianco. Go’then’tag: A 3-d point cloud annotation technique. In *2014 IEEE Symposium on 3D User Interfaces (3DUI)*, pp. 193–194. IEEE, 2014.
- 6) <https://smgcorporateservices.com/industries-served/industrial-buildings>
- 7) Apple Pencil and Scribble – User Interaction – iOS – Human Interace Guidelines – Apple Developer, <https://developer.apple.com/design/human-interface-guidelines/ios/user-interaction/apple-pencil-and-scribble/>